

CARLISLE'S AUTHORIZED APPLICATORS MARKETING ANNOUNCEMENT

ID- 2014-03
SureMB 120TG Base
March 12, 2014

To: Carlisle SynTec Systems' Authorized Applicators

Carlisle SynTec Systems is pleased to introduce SureMB 120TG Base, a torch-grade SBS modified base ply. SureMB 120TG Base adds to Carlisle's line of modified base plies and base sheets, providing owners and specifiers with more options to meet their design criteria. When SureMB 120TG is combined with a Carlisle EPDM, TPO, or PVC cap sheet, it creates an innovative and durable multiple-ply system.

SureMB 120TG can be used as a temporary roof, air barrier, and vapor barrier in Carlisle's traditional single-ply applications. When temperatures and moisture make it difficult for the applicator to use a peel-and-stick vapor barrier or temporary roof, SureMB 120TG is an ideal solution.

Part number	Dimensions	Thickness	Sq. ft. per roll	Rolls per pallet	Weight per roll	Unit of measure
323313	39 3/8" x 32'9"	120 mils	107 sq. ft.	20	85 lbs.	sq. ft.

Carlisle's SureMB 120TG Base is a smooth-surfaced, premium-grade base ply reinforced with a non-woven polyester mat. The combination of the high-performance reinforcing mat and quality SBS elastomers creates a durable and flexible base ply, inter-ply, or temporary membrane.

SureMB 120TG Features and Benefits:

- High puncture and tear resistance
- Can be used as a temporary roof
- Meets UL 790 external fire rating and FM 4470 approvals
- Meets ASTM D6164 requirements
- Eliminates the use of a kettle
- Can be included in Carlisle Warranties of up to 30 years

SureMB 120TG can be torched to structural concrete, DensDeck®, DensDeck® Prime or SECUROCK®. See Carlisle specifications for additional substrate applications. If you have any questions or for more information, please contact your local manufacturer's representative.

Sincerely,



Paul Markel
FleeceBACK® Sales and Marketing